



ElettriKa

**ELECTRIC LOCK
FOR DOORS AND GATES**

CISA "ElettriKa" is the ideal solution for managing the opening and closing of all kinds of doors and gates, guaranteeing high resistance to forced entry.

MAIN FEATURES AND BENEFITS

- Rotary hook deadbolt for increased resistance to forced entry.
- Self-adjustable floor striker ensuring perfect closure over time.
- Steel casing to protect the lock.
- Electric release system for increased resistance to vibrations and impact strength.





Technical features:

- Painted protective steel case
- Metal striker with stainless steel swinging pin
- Rotary hook deadbolt in extruded aluminium
- 12V ac power supply
- Current absorption 3 A
- Non-handed and with a variable backset from 50 to 80 mm

Supplied as standard:

- Striker
- Instruction sheet
- Fixing screws
- 2 spacers for the striker
- 3 keys item 1.01070.10.1

On request:

- Booster device item 1.07022.00.0
- Booster plus device item 1.07022.10.0
- Coil set BTicino device item 1.07025.10.0
- Microswitch device item 1.07023.00.0
- Lighted indicator kit item 1.07126.01.0

Hand:
0 = Non-handed

Certification:

- ELETTRIKA is certified according to the European standard prEN 14846:08:

| 3 | X | 2 | 0 | 0 | M | 6 | 0 | 2 |


- Security degree 6
(2,000 Kg lateral push resistance)

Elettrika



Type	Description	Cylinder	Throws	Backset	Unit weight 	Pieces 	ITEM				
							Type	Dim.	Hand	Fin.	Pers.
	<ul style="list-style-type: none"> • Back plate for lock and striker to be welded 	 Art. 1 0G150 00 0 Fin.12	50÷80	2,750	6	1	1A721 00 0				
	<ul style="list-style-type: none"> • Version with BTicino coil item 1.07025.10.0 		50÷80	2,710	6	1	1A721 00 0 00 PA				
	<ul style="list-style-type: none"> • Version with Booster item 1.07022.00.0 		50÷80	2,710	6	1	1A721 00 0 00 PB				
	<ul style="list-style-type: none"> • Version with Booster Plus item 1.07022.10.0 		50÷80	2,710	6	1	1A721 00 0 00 PC				
	<ul style="list-style-type: none"> • Galvanized version • Welding plate and striker spacer 	 Art. 1 0G150 00 0 Fin.12	50÷80	2,800	1	1	1A721 00 0 79				
	<ul style="list-style-type: none"> • Back plate for lock and striker to be welded • Inner push-button • Hold open device 	 Art. 1 0G150 00 0 Fin.12	50÷80	2,800	6	1	1A731 00 0				
	<ul style="list-style-type: none"> • Version with BTicino coil item 1.07025.10.0 		50÷80	2,800	6	1	1A731 00 0 00 PA				
	<ul style="list-style-type: none"> • Version with Booster item 1.07022.00.0 		50÷80	2,800	6	1	1A731 00 0 00 PB				
	<ul style="list-style-type: none"> • Version with Booster Plus item 1.07022.10.0 		50÷80	2,800	6	1	1A731 00 0 00 PC				
	<ul style="list-style-type: none"> • Galvanized version • Welding plate and striker spacer • Inside button • Hold-open device • Galvanized protective case 	 Art. 1 0G150 00 0 Fin.12	50÷80	2,800	1	1	1A731 00 0 79				

Type	Description	Cylinder	Throws	Backset	Unit weight Kg	Pieces	ITEM					
							Type	Dim.	Hand	Fin.	Pers.	Spec.



- Inner push-button
- SUPPLIED AS STANDARD:
Striker
Weld plate
Weld striker spacer
Strike spacer set (2pcs)
Fixing screws
Keys item 1.01070.10.1
Instruction sheet



Art.
1 06200 55 0 Fin.12

50÷80 2,780 6 1 1A611 00 0 00 DF

Type	Description	Unit weight Kg	Pieces	ITEM			
				Type	Dim.	Hand	Fin.
	<ul style="list-style-type: none"> • Booster device may be combined with ElettriKa rim lock to have the following function: Tension adaptor for tension different from 12 V ac (12 Vdc - 24 Vac - 24Vdc) Electrical input reduction Undersized power supply Electric hold open device (ElettriKa only) • Supplied as standard: Fixing screws Instructions sheet • Please note: Booster device may be combined also with all electric locks (electric striker included) 	0,085	1	1	07022	00	0
	<ul style="list-style-type: none"> • Booster Plus device may be combined with ElettriKa rim lock to have the following function: Electronic opening timer with 5 different options (120 sec default) Door condition signal Electric hold open device Tension adaptor for tension different from 12 V ac (12 Vdc - 24 Vac - 24Vdc) Electrical input reduction Undersized power supply • Supplied as standard: Pin to deactivate hold open catch Fixing screws Instructions sheet • ON REQUEST: Open door indicator item 1.07126.01.0 	0,185	1	1	07022	10	0
	<ul style="list-style-type: none"> • Coil for BTicino intercommunication system audio • Swing ref. 344702-03-04 • Video intercommunication system video Swing ref. 344802-03-04 combined with ElettriKa rim lock give door control signal • Supplied as standard: Fixing screws Instructions sheet 	0,092	1	1	07025	10	0
	<ul style="list-style-type: none"> • Microswitch Give a signal to operate ration motor may be installed directly on the Elettrika rim lock • Supplied as standard: instruction sheet 	0,007	1	1	07023	00	0
	<ul style="list-style-type: none"> • Open door indicator 	0,005	1	1	07126	01	0



Technical features:

- Zinc-plated steel case and striker
- Dead-locking latch
- 12 V ac
- Current absorption 2,5 A
- External cylinder length: 55 mm.

Supplied as standard:

- Striker
- Instruction sheet
- Fixing screws (except series 11921-11931)
- 3 keys item 1.01070.10.1 (C2000 key bow)

On request:

- Booster module item 1.07022.00.0

Certifications:

- This electric lock series is certified according to the European standard EN 14846:08:

| 3 | C | 2 | 0 | 0 | L | 3 | 0 | 2 |

Security degree 3

(500 Kg lateral push resistance and 200 Kg front push resistance)

Hand:

- 1 = R.H. inwards
- 2 = L.H. inwards
- 3 = R.H. outwards
- 4 = L.H. outwards

Type	Description	Cylinder	Throws	Backset	Unit weight	Pieces	ITEM				
							Type	Dim.	Hand	Fin. Pers. Spec.	
<ul style="list-style-type: none"> • Protective back plate • Spacer 	<p>1 02139 00 0</p>	50	2,140	5	1	11721	50	1			
		50	2,140	5	1	11721	50	2			
		60	2,140	5	1	11721	60	1			
		60	2,140	5	1	11721	60	2			
		70	2,140	5	1	11721	70	1			
		70	2,140	5	1	11721	70	2			
		80	2,140	5	1	11721	80	1			
		80	2,140	5	1	11721	80	2			
<ul style="list-style-type: none"> • Protective back plate • Spacer • Push-button • Hold-open device 	<p>1 02110 00 0</p>	50	2,180	5	1	11731	50	1			
		50	2,180	5	1	11731	50	2			
		60	2,180	5	1	11731	60	1			
		60	2,180	5	1	11731	60	2			
		70	2,180	5	1	11731	70	1			
		70	2,180	5	1	11731	70	2			
		80	2,180	5	1	11731	80	1			
		80	2,180	5	1	11731	80	2			
<ul style="list-style-type: none"> • Manual throw deadbolt • Protective back plate • Spacer 	<p>1 02145 00 0</p>	2	50	2,200	5	1	11761	50	1		
		2	50	2,218	5	1	11761	50	2		
		2	60	2,290	5	1	11761	60	1		
		2	60	2,290	5	1	11761	60	2		
		2	70	2,280	5	1	11761	70	1		
		2	70	2,222	5	1	11761	70	2		
		2	80	2,230	5	1	11761	80	1		
		2	80	2,250	5	1	11761	80	2		
		<ul style="list-style-type: none"> • Manual throw deadbolt • Protective back plate • Spacer • Push-button 	<p>1 02145 00 0</p>	2	50	2,205	1	1	11771	50	1
				2	50	2,205	1	1	11771	50	2
2	60			2,280	1	1	11771	60	1		
2	60			2,280	1	1	11771	60	2		
2	70			2,210	1	1	11771	70	1		
2	70			2,210	1	1	11771	70	2		
2	80			2,231	1	1	11771	80	1		
2	80			2,251	1	1	11771	80	2		

Type	Description	Cylinder	Throws	Backset	Kg	Pieces	ITEM				
							Type	Dim.	Hand	Fin.	Pers. Spec.
	<ul style="list-style-type: none"> • For automated and up-and-over gates • Protective back plate • External cylinder length: 70 mm. 		80	2,100	1	1	11823	80	1		
			80	2,100	1	1	11823	80	2		
			50	1,450	1	1	11921	50	1		
			50	1,450	1	1	11921	50	2		
			60	1,559	1	1	11921	60	1		
			60	1,472	1	1	11921	60	2		
			70	1,472	1	1	11921	70	1		
			70	1,476	1	1	11921	70	2		
			80	1,470	1	1	11921	80	1		
			80	1,475	1	1	11921	80	2		
	<ul style="list-style-type: none"> • Push-button • Hold-open device 		50	1,475	1	1	11931	50	1		
			50	1,475	1	1	11931	50	2		
			60	1,550	1	1	11931	60	1		
			60	1,472	1	1	11931	60	2		
			70	1,475	1	1	11931	70	1		
			70	1,478	1	1	11931	70	2		
			80	1,470	1	1	11931	80	1		
			80	1,472	1	1	11931	80	2		
	<ul style="list-style-type: none"> • FOR OUTWARD OPENING GATES 		50	1,539	1	1	11921	50	3		
			50	1,538	1	1	11921	50	4		
			60	1,614	1	1	11921	60	3		
			60	1,534	1	1	11921	60	4		
			70	1,533	1	1	11921	70	3		
			70	1,538	1	1	11921	70	4		
			80	1,539	1	1	11921	80	3		
			80	1,534	1	1	11921	80	4		
	<ul style="list-style-type: none"> • FOR OUTWARD OPENING GATES • Push-button • Hold-open device 		50	1,536	1	1	11931	50	3		
			50	1,530	1	1	11931	50	4		
			60	1,532	1	1	11931	60	3		
			60	1,532	1	1	11931	60	4		
			70	1,530	1	1	11931	70	3		
			70	1,534	1	1	11931	70	4		
			80	1,532	1	1	11931	80	3		
			80	1,532	1	1	11931	80	4		